Patent

32692 Customer Number Case No.: 58446US002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named Inventor:	MEKALA	, David R.
-----------------------	--------	------------

Confirmation No.: 9235 Application No.: 10/666626

1745 Group Art Unit Filed: September 18, 2003

Title FUEL CELL GAS DIFFUSION LAVER

	BRIEF ON APPEAL
Mail Stop: Appeal Brief-Patents Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450	CERTIFICATE OF MAILING OR TRANSMISSION [37 CFR § 1.8(a)] I hereby certify that this correspondence is being: deposited with the United States Postal Service on the date shown below with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450. transmitted by facsimile on the date shown below to the United States Patent and Trademark Office at 571-273-8300. transmitted to United States Patent and Trademark Office on the date shown below via the Office electronic filing system. February 12, 2008 Signed by Phyllis Boettcher
Dear Sir: This is an appeal from the	Office Action mailed on June 13, 2007, finally rejecting claims

1-12 and 30.

<u>Fees</u>

Any required fee under 37 CFR § 41.20(b)(2) will be made at the time of submission via

	EFS-Web. In the event fees are not or cannot be paid at the time of EFS-Web submission, please charge any fees under 37 CFR § 1.17 which may be required to Deposit Account No. 13-3723.
	Please charge any fees under 37 CFR §§ 37 CFR § 41.20(b)(2)1.16 and 1.17 which may be required to Deposit Account No. 13-3723. (One copy of this sheet marked duplicate is enclosed.)
\boxtimes	Please charge any additional fees associated with the prosecution of this application to Deposit Account No. 13-3723. This authorization includes the fee for any necessary extension of time under 37 CFR § 1.136(a). To the extent any such extension should become necessary, it is hereby requested.
\boxtimes	Please credit any overpayment to the same deposit account.

A Notice of Appeal in this application was transmitted on December 13, 2007, and was received in the USPTO on December 13, 2007.

Appellants request the opportunity for a personal appearance before the Board of Appeals to argue the issues of this appeal. The fee for the personal appearance will be timely paid upon receipt of the Examiner's Answer.

REAL PARTY IN INTEREST

The real party in interest is 3M Company (formerly known as Minnesota Mining and Manufacturing Company) of St. Paul, Minnesota and its affiliate 3M Innovative Properties Company of St. Paul, Minnesota.

RELATED APPEALS AND INTERFERENCES

Appellants are unaware of any related appeals or interferences.

STATUS OF CLAIMS

Claims 1-30 are pending. Claims 13-29 are withdrawn. Claims 1-12 and 30 stand rejected and are the subject of the Appeal.

STATUS OF AMENDMENTS

No amendments have been filed after the final rejection.

SUMMARY OF CLAIMED SUBJECT MATTER

The claims at issue concern a fuel cell gas diffusion layer (Specification at p. 4, ln. 19 – p. 5, ln. 24). The gas diffusion layer, or GDL, is a component of a polymer electrolyte membrane fuel cell. The claims at issue concern a GDL that comprises a hydrophilic surface layer (Specification at p. 5, ln 25 – p. 6., ln 21) having a thickness of no more than 0.5 micron (Id.), and, thereunder, a hydrophobic second layer (Specification at p. 5, ln 21 – p. 6., ln. 9) comprising a fluoropolymer (Id.) having a thickness of at least 5 microns (Id.). The application of a hydrophilic surface layer having a thickness of no more than 0.5 micron is enabled throughout the present Specification, including the present Examples (Specification at p. 9, ln. 26 – p. 12, ln 15.)

GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL

Case No.: 58446US002

First Ground of Rejection

Claims 1-4, 6 and 30 stand rejected under 35 USC § 103(a) as purportedly unpatentable over WO 03/058743 (Barton) taken alone.

Second Ground of Rejection

Claims 5-7 stand rejected under 35 USC § 103(a) as purportedly unpatentable over Barton taken alone.

Third Ground of Rejection

Claims 8-10 stand rejected under 35 USC § 103(a) as purportedly unpatentable over Barton taken alone and further in view of JP 11-045733 (Nagamori).

Fourth Ground of Rejection

Claim 11 stands rejected under 35 USC § 103(a) as purportedly unpatentable over Barton taken alone and further in view of WO 02/022952 (Segit).

Fifth Ground of Rejection

Claim 12 stands rejected under 35 USC § 103(a) as purportedly unpatentable over Barton taken alone and further in view of US 6,083,638 (Taniguchi).

ARGUMENT

Regarding All Grounds of Rejection

Each of the present rejections relies on a purported disclosure in Barton of a fuel cell gas diffusion layer ("GDL") bearing a hydrophilic layer with a thickness of "about 1 to about 100 microns, preferably between about 8 and about 16 microns." (Barton at page 14, lines 18-20). This purported disclosure does not anticipate or render obvious the present claims, since the present claims recite a fuel cell GDL having "a hydrophilic surface layer having a thickness of no more than 0.5 micron." (present Claim 1) As the Examiner admits, Barton fails to teach this limitation anywhere. However, not only does Barton fail to teach or suggest this limitation, Barton teaches away from this limitation, since Barton recites a preferred thickness of "between about 8 and about 16 microns." (Id.). This lack of any teaching or suggestion in Barton of "a hydrophilic surface layer having a thickness of no more than 0.5 micron" (present Claim 1) is not surprising, since Barton does not appear to enable a fuel cell GDL having such a thin a hydrophilic surface layer.

The Examiner admits that "Barton does not expressly teach a hyrophilic surface layer that has a thickness of no more than 0.5 micron." (June 13 Office Action at page 3, lines 8-9). However, the Examiner does not address the *express teaching away* from this limitation in Barton, where Barton recites a preferred thickness of "between about 8 and about 16 microns." (Barton at page 14, lines 18-20). The Examiner asserts that the 0.5 micron limitation found in the present claims could be found by routine experimentation to optimize a result effective variable based on the teaching of Barton. However, 1) Barton in fact teaches a very broad range of values for that variable (1-100 microns), 2) Barton also teaches a very broad range of *preferred* values for that variable (8-16 microns), 3) the present claim limitation lies well outside all of the broad ranges recited in Barton for that variable, and 4) the recitation of the preferred range in Barton is a clear teaching *away* from the present claim limitation and the present invention.

Furthermore, it does not appear that the very thin hydrophilic surface layer required in the present claims is enabled in Barton. Barton purportedly teaches formation of a hydrophilic layer by coating a slurry or solution (Barton at p. 13, ln. 20 - p. 14, ln. 5) and purports to exemplify the use of rod coating (Barton at p. 17, ln. 25 - p. 20, ln. 38). In contrast, one method of forming so

Case No.: 58446US002 Application No.: 10/666626

thin a hydrophilic layer taught in the present Specification involves plasma treatment of the surface of a GDL. While the present claims contain no process limitations and are not limited to the use of any process in particular, it does not appear that the very thin hydrophilic surface layer required in the present claims is enabled in Barton.

For all these reasons, the rejection of claims 1-12 and 30 under 35 USC § 103 should be reversed.

CONCLUSION

For the foregoing reasons, appellants respectfully submit that the Examiner has erred in rejecting this application. Please reverse the Examiner on all counts.

Respectfully submitted,

February 12, 2008

Date

Philip Y. Dahl, Reg. No.: 36,115

Telephone No.: 651-737-4029

Office of Intellectual Property Counsel 3M Innovative Properties Company Facsimile No.: 651-736-3833

CLAIMS APPENDIX

Claims involved in the Appeal:

1. (Previously Presented) A fuel cell gas diffusion layer comprising a hydrophilic surface layer having a thickness of no more than 0.5 micron, and, thereunder, a hydrophobic second layer comprising a fluoropolymer having a thickness of at least 5 microns.

- 2. (Original) The fuel cell gas diffusion layer according to claim 1 wherein said hydrophobic second layer comprises dispersed particles of carbon and a fluoropolymer.
- 3. (Original) The fuel cell gas diffusion layer according to claim 1 wherein said hydrophobic second layer comprises a carbon fiber construction coated with a fluoropolymer.
- 4. (Original) The fuel cell gas diffusion layer according to claim 1 additionally comprising a supporting third layer underlying said second layer.
- 5. (Original) The fuel cell gas diffusion layer according to claim 4 wherein said supporting third layer comprises a carbon fiber construction coated with a fluoropolymer.
- 6. (Original) The fuel cell gas diffusion layer according to claim 2 additionally comprising a supporting third layer underlying said second layer.
- 7. (Original) The fuel cell gas diffusion layer according to claim 6 wherein said supporting third layer comprises a carbon fiber construction coated with a fluoropolymer.
- 8. (Original) The fuel cell gas diffusion layer according to claim 1 wherein said hydrophilic surface layer comprises functional groups containing Si or a metal.
- 9. (Original) The fuel cell gas diffusion layer according to claim 1 wherein said hydrophilic surface layer comprises functional groups containing Si.

10. (Original) The fuel cell gas diffusion layer according to claim 1 wherein said hydrophilic surface layer comprises functional groups containing Si and O.

- 11. (Original) A roll good comprising the fuel cell gas diffusion layer according to claim 1.
- 12. (Original) The fuel cell gas diffusion layer according to claim 1 wherein said hydrophilic surface layer is present on less than all of said hydrophobic second layer, according to a pattern.
- 30. (Original) A fuel cell electrode comprising the fuel cell gas diffusion layer according to claim 1 and a layer of fuel cell electrode catalyst in contact with said hydrophilic surface layer.

EVIDENCE APPENDIX

None.

RELATED PROCEEDINGS APPENDIX

None.